

Type Approval Certificate



Germanischer Lloyd

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 850 - 07 HH

Company Reichle & De-Massari AG
Binzstrasse 31
8622 Wetzikon, SWITZERLAND

Product Description Connection System RJ45 Cat. 5e/s consisting of Connection Module Cat.5e, 1xRJ45/s and diverse Patch Cords Cat. 5e

Type Connection Modul Cat.5e, 1 x RJ45/s and /u
Patch Cord Cat. 5e/s and /u; CP Cable Cat. 5e/s and /u

Environmental Category D

Technical Data /
Range of Application

Mechanical data:
Pole count: 8
Operating temperature: -10° C to 60° C
Humidity: 95 % (non condensing)
Hausing material: Polycarbonate (UL-94-V0)
Admissible wire: 0,5 mm (AWG24) - 0,65 mm (AWG22)
Admissible insulation: 0,8 mm - 1,6 mm

Electrical data:
Contact resistance: < 300 mΩ
Transfer impedance: 1 MHz < 100 mΩ
10 MHz < 200 mΩ
30 MHz < 620 mΩ

Further technical datas according to the manufacturer's data sheet

Type variants, Assemblies and patch cords see page 2

Test Standard Guidelines for the Performance of Type Approvals Part 2, Edition 2003
IEC 60603-7:2002; ISO/TEC 11801:2002; EN 50173-1:2002

Documents Test report : TL020.291_b, dated 21.06.2007
TL020291_c, dated 21.06.2007
ZT 020.091, dated 26.09.2002

Remarks None

Valid until 2012-07-17

Page 1 of 2

File No. I.N.02

Hamburg, 2007-09-13

Type Approval Symbol



Germanischer Lloyd

i.v. w.v. d.
Wolfgang Voß

R. Fenster
Reinhard Fenster



Germanischer Lloyd

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 850 - 07 HH

Types/Assecories: Modul Cat.5e 1xRJ45/s
Module Cat. 5e 1xRJ45/s Snap / in
Module Cat. 5e 1xRJ45/s Special
Module Cat. 5e 1xRJ45/s Flap-Jack
Module Cat. 5e 1xRJ45/u
RJ45 Couple module, Cat.5e
RJ45 Connection module, accessories

Patch Cords Cat. 5e: The patch cords are used for connecting the network equipment to patch panels and telecommunications outlets, and cross connection between various applications and end users.

Types: Patch Cord Cat. 5e/s
Patch Cord Cat. 5e/u
CP Cable Cat. 5e/s and /u

Lengths: 0,5 m to 75 m

Patch Cord Characteristics: UTP/

S-FTP

Inner conductor diameter: Stranded copper AWG 26
Number of pairs: 4
Screen 1 pair: None
outer screen: None
Jacket: PVC
Overall diameter: 5,1 mm
Bend Radius: 25 mm

Stranded copper AWG26
4
None
Cu-braid + Al/polyester foil
PVC or LSFROH
5,5 mm
30 mm

Valid until 2012-07-17

Page 2 of 2

Type Approval Symbol



File No. I.N.02

Hamburg, 2007-09-13

Germanischer Lloyd

Wolfgang Voß

Reinhard Fenster

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".