

**R314294 Splice Closure FL, 72 splices, Ø155x332, 1xoval 4xØ20**

010.2438 Similar product

**Scope of supply**

- Complete splice closure, excluding splice trays

**Weight**

2565.000G

**Technical Data**

|                                   |                                |
|-----------------------------------|--------------------------------|
| Distributor, housing type         | Splice closure                 |
| Number of fibers / conductors     | 72                             |
| Color code RAL                    | 9005                           |
| Color                             | jet black                      |
| Lockable (yes/no)                 | Yes                            |
| Splice closure valve              | Yes                            |
| Splice closures grounding         | Yes                            |
| Splice closures wall/pole holder  | No                             |
| Splice closures with shrink tubes | Yes                            |
| Dimensions                        | Ø 155 x 332 mm (1xoval, 4xØ20) |
| Material                          | plastic: HD-PE                 |
| Protection class (IP)             | 68                             |

**Tender text**

FO Splice Closure for max. 72 fibers, type FL  
FO dome-end closure for max. 72 splice connections, featuring a mechanical locking system, suitable for cable-to-cable splicing with fiber branching and fiber-in-the-loop applications (uncut cables), individual strain relief for each cable, splice tray with loose tubes storage, repeated opening does not wear off the sealing material, the locking system offers sealing and locking option, continuous ground connection, valve for leak testing. Closure body and flange are made of HD polyethylene, and the turnlock fastener of fiberglass-reinforced PE, resistant to alkaline earths, salt water, fungal and putrefaction bacteria, strain relief ring and splice tray holder are made of stainless steel. The splice closure can be used in ambient temperatures of -20 to +60° Celsius and water depths of 6 meters (IP68). The closure can be equipped with either 6 splice trays R30 or 3 splice trays R40.

**Modules & Accessories**

|         |   |
|---------|---|
| R30392  | Desiccant (silica gel), 2x 60g                    |
| R307029 | Strain Relief Kit, Splice Closures                |
| R307321 | Shrink Tube Kit, Ø31/8x150                        |
| R307323 | Shrink Tube Kit Oval, Ø75/23x150                  |
| R307319 | Transport Kit, 72 splice connections              |
| R30393  | Splice Tray Basic Set R30, white                  |
| R30394  | Splice Tray Additional Set R30, white             |
| R308445 | Splice Tray Basic Set R40                         |
| R308444 | Splice Tray Additional Set R40                    |
| R303002 | Shield Connection Cable V-shape / Ø 6 mm, 400 mm  |
| R303003 | Shield Connection Cable V-shape / V-shape, 500 mm |
| R308561 | Grounding Kit for Steel-Armored Cables Ø 22-6 mm  |
| R308562 | Grounding Kit for Steel-Armored Cables Ø 32-10 mm |
| R307316 | Wall and Pole Mounting Kit, Closures Ø 160 mm     |
| R308097 | Reserve Box for Excess Cable                      |