

R500532 19" 1U Angled Patch Panel 24xRJ45/u, Cat.6, gray, fully populated

090.5048

**Scope of supply**

- 19" 1U 24-port angled, metal patch panel, empty, integrated cable tie shelf
- 24 Cat.6 connection modules, RJ45/u incl. dust covers
- 19" mounting kit
- Labeling kit
- Cable ties
- Installation instructions

Weight

1151.000G

Technical Data

Standardisation	IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801 ed. 2.2: June 2011; EN 50173-1: May 2011;
Fastening (inch)	19"
Height Units (U)	1
Rack mounting version	Patch Panel
Capacity (ports)	24
Number of connectors (A)	24
Connector type (A)	RJ45
Category connector (A)	Cat.6
Shielding - connector (A)	No
Protection class (IP) connector (A)	20
Holder for connector / module	Snap-In Frame
Color	steel: blue, chromitized / front: gray (NCS 2502-B)
Assembly	fully populated
Dimensions	43.2 x 482.6 x 245.3 mm
Material	steel: DC01 (1.0330), 1.5 mm

Tender text

19" 1U Angled Patch Panel, 24 x RJ45, Cat.6, unshielded

Angled patch panel with integrated cable tie shelf, 19" fastening kit, labeling field, accepting the snap-in type color coding clips in 8 colors.

Material: sub-rack made of sheet steel (DC01) 1.5 mm, color blue chromated, screen made of plastic (ABS), halogen-free, color medium gray (NCS 2502-B)

Populated with 24 unshielded RJ45 connection modules of Category 6, for the establishing of transmission channels of class E with up to 4 plugged connections, complies with Category 6 requirements of the standards ISO/IEC 11801 ed. 2.2, June 2011, EN 50173-1, May 2011 (DIN EN 50173-1) as well as ANSI/TIA/EIA 568C, de-embedded tested in acc. with IEC 60603-7-4, interoperable and backwards compatible with Cat.5e and Cat.5.

Suitable for 10GBase-T applications in acc. with IEEE 802.3an up to 500 MHz and 55 m.

Tested in line with R&M's manufacturing control, performing 100% inspection.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), PCB-free and tool-free Easy-Lock connection of installation cables AWG 24 – 22 (0.5 mm – 0.65 mm) and flexible cables AWG 26/7 – AWG 22/7. Parallel pair termination without crossover in acc. with EIA/TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance 1000 Veff. Halogen-free materials. With integral cable strain relief, including dust cover.

Mounting dimensions 14.9 x 19.5 mm, max. material thickness 1.6 mm.

Connection module Cat.6, unshielded, with dust cover, snap-in frame, cable tie and installation instructions.

Modules & Accessories

R308708	Snap-in Blind Cover, light gray
R302151	Snap-in Coding Clip, anthracite
R302152	Snap-in Coding Clip, blue
R302153	Snap-in Coding Clip, brown
R302154	Snap-in Coding Clip, green
R302155	Snap-in Coding Clip, red
R302156	Snap-in Coding Clip, violet
R302157	Snap-in Coding Clip, white
R302158	Snap-in Coding Clip, yellow
R804261	Snap-in Coding Clip, black
R500542	1U Angled Steel Panel
R502913	19" 1U Angled Patch Panel, Cover